

SPECIFICATION(15000NW)

Rated line pull	15000 lbs (6810kgs)
Motor displacement	160ml/r
Oil flow	5~60L/min
Pressure	16Mpa
Gear reduction ratio	17.2:1
Cable (Dia. × L)	Ø15/32" × 86.9' (Ø12mm × 26.5m)
Drum size(Dia. × L)	Ø5.0" × 10.5" (Ø127mm × 266mm)
Mounting bolt pattern	12.0" × 4.5" (303.5mm × 114.3mm) ; 14.5" × 6.7" (368.5mm × 171.2mm) 8-M12
Overall dimensions (L × W × H)	28.5" × 12.3" × 12.0" 723mm × 312mm × 304mm
Net weight lbs(kg)	227lbs(103kg)

Pull , Speed, Pressure, Flow (First layer)

Line pull lbs (kgs)	Pressure Mpa(Psi)	Flow G/min (L/min)	Line speed ft/min(m/min)
0	2.0(290)	2.6(10)	4.2(1.3)
4000(1814)	4.6(668)	5.3(20)	8.5(2.6)
6000(2722)	6.9(1003)	7.9 (30)	12.4(3.8)
8000(3629)	9.2(1337)	10.6(40)	16.7(5.1)
10000(4536)	11.5(1672)	13.2(50)	21(6.4)
12000(5448)	14.0(2030)	/	/
15000(6810)	17.5(2537)	/	/

Line Pull And Rope Capacity Inlayer

Layer of wire rope	Rated line pull lbs(kgs)	Total rope on drum ft (m)
1	15000(6810)	29.5(9.0)
2	12791(5807)	65.6(20.0)
3	11150 (5062)	86.9(26.5)